Industrial Tracker



\land Features

- EU, US, and Asia frequency supported
- LoRaWAN 1.0.3
- High resolution GNSS module
- IP66 equivalent



The Industrial Tracker is a general purpose tracker, designed for GPS tracking on various applications: bicycles, cars or pets. It is equipped with GPS and 3-axis accelerometer, that provides a much more cost-effective way for service providers to deploy this for tracking applications than to use GPRS network.

Specification				
Model Name	WSMS-141			
Frequency	Either 863–870MHz for EU models and 902–928MHz for North America			
RF TX power	+19dBm conducted			
Antenna Gain	0dBi Peak, -3dBi Avg			
RF Sensitivity	-138dBm conducted			
Battery Type	3.6V ½ AA Li-SOCl2 1200mAh battery (*2) (ER14250)			
Voltage	3.1~3.6 V			
Average Current	170mA maximum/5uA minimum			
Operation Temperature	-20°C to +70°C			
Environmental Rating	IP 66 equivalent			
Sensor	GNSS module, 3D MEMs accelerometer, Hall-effect			
Dimensions	107mm x 52mm x 27mm			
Weight	45g			
PCB Temperature	NTC 100k ohm			
Battery Monitoring	Resistor divider			
Type Approval	FCC/IC			

Industrial Tracker

SKU Detail				
SKU	Country	Channels	Frequency Band (MHz)	
TNIT100-868	Europe	8	EU868 (862~870)	
TNIT100-915	USA	16	US915 (902~928)	

